Python praktikum

Alessandro Mammana 10.10.2014 Max Plank Institute for Molecular Genetics

Praktikum layout

- introduction and "finger exercises" (2-3 hours)
- let's go to eat something
- guided problem (1-2 hours)
- free time (until 18:00)

Python: pros and cons

- Pros:
 - easy to write and to read
 - interactive
 - general-puropse programming language
- Cons:
 - not as fast as C, C++ and Java (but faster than R)
 - not suitable for very large projects

Easy to write and to read

```
def sort(array):
    if (len(array) <= 1):
        return array
    less = []
    equal = []
    greater = []
    pivot = array[0]
    for x in array:
        if x < pivot:
            less.append(x)
        if x == pivot:
            equal.append(x)
        if x > pivot:
            greater.append(x)
    return sort(less)+equal+sort(greater)
```

Python is interactive

~> python3

```
Python 3.3.0 (default, Dec 5 2012, 11:05:54)
[GCC 4.7.1] on linux
Type "help", "copyright", "credits" or "license" for more information.
>>> print("Hello Python!")
Hello Python!
>>>
```

Python is general-purpose

- You are not going to use python only for bioinformatics
- Applications:
 - very good for scripting
 - scientific computing (numpy and scipy)
 - developing web applications (django)
 - plugins of many applications can be written in python (e.g. inkscape)

Interactive computing, scripting, programming

1. Interactive computing

```
~> python3
Python 3.3.0 (default, Dec 5 2012, 11:05:54)
[GCC 4.7.1] on linux
Type "help", "copyright", "credits" or "license" for more information.
>>> print("Hello Python!")
Hello Python!
>>> quit()
```

2. Scripting:

~> mkdir pyprakt ~> cd pyprakt ~/pyprakt> gedit code.py &			
<pre>print("hello world!")</pre>			
~/pyprakt> python3 code.py hello world!			
	or:		
<pre>#!/usr/bin/python3 print("hello world!")</pre>			
~/pyprakt> ./code.py			

hello world!

Interactive computing, scripting, programming

3. Programming

```
import sys #importing module
def imHappy(n): #function definition
  for i in range(n): #indent code using spaces or a tab
    print("Hello Python!")
```

if __name__ == "__main__": #make the python program runnable from terminal imHappy(int(sys.argv[1]))

~/pyprakt> python3 code.py 3
"Hello Python!"
"Hello Python!"
"Hello Python!"
~/pyprakt> python3

```
Python 3.3.0 (default, Dec 5 2012, 11:05:54)
[GCC 4.7.1] on linux
Type "help", "copyright", "credits" or "license" for more information.
>>> import code
>>> code.imHappy(3)
"Hello Python!"
"Hello Python!"
```

No coding, no learning

- we will play with python in interactive mode
- we will write functions in gedit (or any text editor)
- keep 2 windows open, one for python's terminal, one for the editor
- how to modify/add functions in scratchpad.py and reload them:

```
import sys
def imHappy(n):
    for i in range(n):
        print("Good morning Python!") #we modified the code!

if __name__=="__main__":
        imHappy(sys.argv[1])
```

>>> import imp
>>> imp.reload(code) #reload an already imported module, don't forget it!
>>> code.imHappy(3)
"Good morning Python!"
"Good morning Python!"

Python as a calculator

- Syntax as most other programming languages
- two main numeric types: int and float
- powers with the ** operator
- import the math module for more advanced functions

```
>>> 2 + 2 # int + int = int
4
>>> 50 - 5*6
20
>>> (50 - 5.0*6)/4 # float
5.0
>>> 8/5.0 #float
1.6000000000000000
>>> 8//5 #integer division
1
>>> 17 // 3.0 #explicit integer division
5.0
>>> 5 * 3 + 2 # result * divisor + remainder
17
>>> 5 ** 2 # 5 squared
25
>>> 2 ** 7 # 2 to the power of 7
128
>>> import math
>>> math.sqrt(40)
6.324555320336759
>>> math.cos(2*math.pi)
1.0
```

Assigning to a variable

- the equal sign (=) is used for variable assignment
- variables need to be defined before they are used
- multiple assignment

```
>>> width = 20
>>> height = 5*9
>>> width*height
900
>>> n
Traceback (most recent call last):
   File "<stdin>", line 1, in <module>
NameError: name 'n' is not defined
>>> a, b, c = 1, 2, 3 #multiple assignment
>>> b
2
>>>
```

Warming up

compute the following number:

$$\cos\left(\pi \frac{12^{1.5} + 4^2 + 3^3}{42}\right)$$

>>> math.cos(math.pi*(12**(1.5) + 4*4 + 3**3)/42) 0.9990937147385679

Sequence types

Arrays in different flavours

- Strings: sequence of characters
- Lists: mutable sequence of arbitray objects
- Tuples: immutable sequence of arbitrary objects
- Ranges: implicit sequence of consecutive numbers

They all support random access (like arrays) and many other things

```
>>> msg = "Python : <3"
>>> msg[0]
'P'
>>> msg[1]
'y'
>>> len(msg)
11
```

Strings

To define a string

- Enclose it in single quotes 'text'
- Enclose it in double quotes "text"
- if the text contains also quotes, escape them with \
- strings are immutable (cannot be modified)

```
>>> 'coding like a boss' #single guotes
'coding like a boss'
>>> 'doesn\'t' #use \ to escape the single quote
"doesn't"
>>> "doesn't" #no need to escape single quotes inside double quotes
"doesn't"
>>> '"Yes," he said.' # no need to escape double quotes inside single quotes
'"Yes," he said.'
>>> "\"Yes,\" he said."
'"Yes," he said.'
>>> '"Isn\'t," she said.'
'"Isn\'t," she said.'
>>> secret = "this is not going to work"
>>> secret[0] = 'W'
Traceback (most recent call last):
 File "<stdin>", line 1, in <module>
TypeError: 'str' object does not support item assignment
```

Lists

- General-purpose array
- Comma-separated items between square brackets
- Elements can have different types
- lists are mutable
- to add an element, use the append function
- lists can be nested to any depth

```
>>> a = ['bio', 'inf', 100, 1234]
>>> a
['bio', 'inf', 100, 1234]
>>> a[1] = 'madness' #lists are mutable
>>> a
['bio', 'madness', 100, 1234]
>>> a.append("rock'n'roll") #append function
>>> a
['bio', 'madness', 100, 1234, "rock'n'roll"]
>>> a.append(['another', 'list']) #nested list
>>> a
['bio', 'madness', 100, 1234, "rock'n'roll", ['another', 'list']]
>>> b = [2, 'nested', 'lists:', a]
>>> b
[2, 'nested', 'lists:', ['bio', 'madness', 100, 1234, "rock'n'roll", ['another', 'list']]]
>>> b[3][1] #nesting list is a way of creating matrices
'madness'
```

Tuples

Difference compared to lists:

- round brackets instead of square brackets
- immutable
- can be converted to lists using the list() function

```
>>> a = ('bio', 'inf', 100, 1234)
>>> a
('bio', 'inf', 100, 1234)
>>> a[1] = 'madness' #lists are immutable
Traceback (most recent call last):
   File "<stdin>", line 1, in <module>
TypeError: 'tuple' object does not support item assignment
>>> a = list(a)
>>> a[1] = 'madness'
>>> a
['bio', 'madness', 100, 1234]
```

The beauty of slicing with python

Python supports very powerful slicing (subsetting) operators

• to count elements from the end, use negative indices

```
>>> mystr = '12345'
>>> mystr[-1] #same as mystr[len(mystr)-1], but much nicer!
'5'
>>> mystr[-3]
'3'
>>> mylist = [1,2,3,4,5]
>>> mylist[-3]
3
```

- to subset use [start:end]
- start defaults to 0, end defaults to the sequence length
- can also specify a step [start:end:step]

```
>>> mytuple = ("don't", "slice", "me", "please")
>>> mytuple[1:3] #start is included, end excluded
('slice', 'me')
>>> mytuple[1:-1] #negative indices can be mixed with positives
('slice', 'me')
>>> mylist[2:] #same as mylist[2:len(mylist)]
[3, 4, 5]
>>> mylist[:2] #same as mylist[0:2]
[1, 2]
>>> mylist[:] #same as mylist[0:len(mylist)] <- good for copying sequences
[1, 2, 3, 4, 5]</pre>
```

Slicing and combining

- with the + operator, strings, tuples and lists can be combined
- with the * operator, strings, tuples and lists can be repeated
- with lists, whole slices can be replaced

```
>>> "that's " + "very " + "intuitive" # + for combining sequences
"that's very intuitive"
>>> mystr = "sliced and combined like a toy"
>>> mystr[:6] + mystr[6:]
'sliced and combined like a toy'
>>> mystr[11:19] + mystr[6:11] + mystr[:6] + mystr[19:]
'combined and sliced like a toy'
>>> "that's " + "very "*3 + "intuitive" # * for repeating sequences
"that's very very very intuitive"
>>> [1]*1 + [2]*2 + [3]*3 + [1,2,3]*3
[1, 2, 2, 3, 3, 3, 1, 2, 3, 1, 2, 3, 1, 2, 3]
>>> surprise = [1,2,3,4]
>>> surprise[3:] = [1,4,9] #that's not the same as: surprise[3] = [1,4,9]
>>> surprise
[1, 2, 3, 1, 4, 9]
>>> surprise[2:-2] = ["who", "put", "me", "there?"]
>>>
>>> surprise
[1, 2, 'who', 'put', 'me', 'there?', 4, 9]
```

- we store paths to fasta files in python strings. Every path ends in ".txt". Write a function that takes in such a path and changes its ending in ".fasta"
- Example: >>> fixEnding("path/to/myfasta.txt") path/to/myfasta.fasta

```
def fixEnding(fapath):
    return fapath[:-3] + "fasta"
```

• we store reads from a sequencing experiment in python strings. read quality often gets worse at the ends of the read. Write a function that takes as input a string and a number n and cuts away the first n and the last n bases/characters.

```
Example: >>> cutReadEnds("AAATACGTGAAACATAAA", 3)
"TACGTGAAACAT"
```

```
def cutReadEnds(read, n):
    return read[n:-n]
```

write a function that creates a list with n zeros

Example

٠

>>> zeros(4) [0,0,0,0]

def zeros(n):
 return [0]*n

- Write a function that takes in a list and returns a tuple with two lists: the even elements and the odd elements of the original list
- Example:

```
>>> mylist = ['one', 1, 'two', 2, 'three', 3, 'four', 4]
>>> magicSplit(mylist)
(['one', 'two', 'three', 'four'], [1, 2, 3, 4])
```

```
def magicSplit(mylist):
    return (mylist[::2], mylist[1::2])
```

Booleans

- 'True' or 'False' keywords
- They work as you would expect
- boolean operators are more readable than in almost all other languages
- boolean operators convert any object to a boolean
- the keyword 'None' is normally to encode special values, it is converted to 'False'
- Empty sequences are also converted to 'False', anything else behaves like 'True', but it's not converted

```
>>> 1>4 # comparisons return booleans
False
>>> 1>4 or 5>4 # 'or', 'and' are much more readable than '||' and '&&' (Java, C, C++, R)
True
>>> False and 5>4
False
>>> False or 5>4
True
>>> None or False # None gets converted to False
False
>>> [] or False # empty sequence gets converted to False
False
>>> "" or False
False
>>> [3,2] or False # anything else behaves like True, but it's not converted
[3, 2]
>>> "anything else" or False
'anything else'
```

If statements and while loops

- Just be careful to the intendation
- 'else if' in python is 'elif'
- the 'while' loop is how you expect

```
>>> if True:
        print("I love Python") #careful to the indentation!
I love Python
>>> if False:
        print("Python is hard to learn")
>>> x = int(input("Please enter an integer: "))
Please enter an integer: 42
>>> if x < 0:
\mathbf{x} = \mathbf{0}
      print('Negative changed to zero')
... elif x == 0:
        print('Zero')
\dots elif x == 1:
        print('Single')
... else:
        print('More')
. . .
More
>>> a, b = 0, 1 #Fibonacci series
>>> while b < 10: #while loop, again, it must be indented!
       print(b)
. . .
      a = b
. . .
       b = a+b
. . .
. . .
1
2
4
8
```

for loop

- The 'for' statement loops over the elements of a sequence
- How to get the "traditional" for loop over a range of numbers?
 - the range() function creates a range of consecutive numbers (efficiently)

```
>>> for i in 'string, list, tuple, range...\n':
        print(i, end="") #variable 'i' takes on all the characters in the sequence
. . .
string, list, tuple, range...
>>> nums = [1, 2, 3, 4]
>>> for i in nums:
       print(i**2)
. . .
1
4
9
16
>>> for i in range(3): #traditional foor loop
        print("Hello Python")
. . .
Hello Python
Hello Python
Hello Python
>>> for i in range(len(nums)):
        nums[i] = nums[i]**2
. . .
>>> nums
[1, 4, 9, 16]
>>> #in java:
>>> #for (int i = start; i < end; i+=step){</pre>
         print(i)
>>> #
>>> #}
>>> #in python:
>>> start, end, step = 0, 6, 2
>>> for i in range(start, end, step):
        print(i)
. . .
```

- Write a function that takes in two numbers 'a' < 'b' and returns a list with all consecutive numbers from 'a' to 'b' ('b' escluded) squared
- Example:

>>> squareList(1, 4) [1, 4, 9]

```
def squareList(a, b):
    res = []
    for i in range(a, b):
        res = res + [i*i]
    return res
#or... better and faster with append()
def squareList(a, b):
    res = []
    for i in range(a, b):
        res = res.append(i*i)
    return res
#or... making a large-enough list before the loop
def squareList(a, b):
    res = list(range(a,b))
    for i in range(len(res)):
        res[i] = i*i
    return res
```

- Write a function that takes to integers 'nrow' and 'ncol' and returns a matrix of zeros with nrow rows and ncol columns. Implement the matrix as a list of lists, where the nested lists are the rows.
- Example:

```
def makeMat(nrow, ncol):
    mat = []
    for i in range(nrow):
        row = []
        for j in range(ncol):
             row.append(0)
        mat.append(row)
    return mat
#we can do it in less lines!
def makeMat(nrow, ncol):
    mat = []
    for i in range(nrow):
        mat.append([0]*ncol)
    return mat
#but this is going to be wrong... why?
def makeMat(nrow, ncol):
    return [[0]*ncol]*nrow
```

[[0,0,0,0], [0,0,0,0]]

• The factorial (in German Fakultaet) function is defined like this:

0! = 1

n! = 1*2*3*...*n

• write a function that takes an integer n and returns the factorial

```
>>> fact(0)
   Example:
•
                     1
                     >>> fact(4)
                     24
                     >>> fact(35)
                     26525285981219105863630848000000
 #Solution 1:
 def fact(n):
      res = 1
      for i in range(1,n+1):
          res *= i
      return res
 #Solution 2:
 def fact(n):
      res = 1
      while (n > 0):
          res *= n
          n -= 1 #in python there is no n++ or n--
      return res
```

- The Euclid algorithm computes the greatest common divisor between two stictly positive integers 'a' and 'b'. It goes like this:
 - 1. if 'b' is equal to zero, the result is 'a', otherwise
 - 2. compute the remainder between 'a' and 'b'
 - 3. replace 'a' with 'b'
 - 4. replace 'b' with the remainder just computed, go back to step 1
- Example:



```
def gcd(a, b):
    while (b != 0):
        tmp = a % b
        a = b
        b = tmp
    return a
```

List comprehension

- very often we need to create a list with a for loop
- because Python requires to indent the code, we need at least 3 lines of code
- but Python also has a solution to this: list comprehension
- it reduces 3 lines to only 1, and it's readable!!!
- the statement can be extended to have nested for loops and an if statement

```
>>> mylist = []
>>> for i in sequence:
    mylist.append(fun(i))
. . .
>>>
>>> mylist = [fun(i) for i in sequence]
>>>
>>> mylist = []
>>> for a in seq1:
    for b in seq2:
     for c in seq3:
       if test(a, b, c):
            mylist.append(fun(a, b, c))
. . .
>>>
    mylist = [fun(a,b,c) for a in seq1 for b in seq2 for c in seq3 if test(a,b,c)]
>>>
```

• rewrite the functions squareList and makeMat in one line

```
def squareList(a, b):
    return [i*i for i in range(a,b)]
def makeMat(nrow, ncol):
    return [[0]*ncol for i in range(nrow)]
```

Write a function that combines every pair of elements from two lists into a list of tuples (of length 2), provided that the elements are not the same

```
• Example: >>> magicComb([1,2,3],[3,1,4])
[(1, 3), (1, 4), (2, 3), (2, 1), (2, 4), (3, 1), (3, 4)]
```

```
#Solution (without list comprehension):
def magicComb(list1, list2):
    combs = []
    for x in list1:
        for y in list2:
            if x != y:
                combs.append((x, y))
    return combs
#Solution (one-liner):
def magicComb(list1, list2):
    return [(x, y) for x in list1 for y in list2 if x != y]
```

• Write a function to transpose a matrix, implemented as before (list of rows)

```
• Example: >>> code.transpose([[1,2,3,4],[5,6,7,8],[9,10,11,12]])
[[1, 5, 9], [2, 6, 10], [3, 7, 11], [4, 8, 12]]
```

```
#Solution 0:
def transpose(mat):
    nrow = len(mat)
    ncol = len(mat[0])
    tmat = []
    for i in range(ncol):
        row = []
        for j in range(nrow):
             row.append(mat[j][i])
        tmat.append(row)
    return tmat
#Solution 1:
def transpose(mat):
    tmat = []
    for i in range(len(mat[0])):
        tmat.append([row[i] for row in matrix])
    return tmat
#Solution 2:
#shorter but not necessarily better than solution 1, it is not very readable
def transpose(mat):
    return [[row[i] for row in mat] for i in range(len(mat[0]))]
```

Dictionaries

- Very powerful, 'pythonic' object (not only in Python)
- A dictionary contains items: item=(key, value)
- · values can be read, modified, inserted and deleted efficiently using their keys
- it is easy to loop through the keys, or the items
- different types in the keys or in the values can be mixed, but lists cannot be used as keys (they are not hashable)

```
>>> emptyDict = {}
>>> tel = {'jack': 4098, 'sape': 4139}
>>> tel['guido'] = 4127 #inserting an item
>>> tel
{'jack': 4098, 'sape': 4139, 'guido': 4127}
>>> tel['jack'] #reading an item
4098
>>> del tel['sape'] #deleting an item
>>> tel['guido'] = 3227 #modifying an item
>>> tel
{'jack': 4098, 'guido': 3227}
>>> tel['angelinajolie'] #key not present
Traceback (most recent call last):
 File "<stdin>", line 1, in <module>
KeyError: 'angelinajolie'
>>> for key in tel.keys(): #same as: for key in tel:
. . .
       print(key)
. . .
jack
quido
>>> for key, value in tel.items():
       print(key, value)
. . .
. . .
jack 4098
guido 3227
>>> dict = {'Name': 'Zara', 'Age': 7, 'Class': 'First', 1:18, 19.2:"that's a weird key..."} #mixed key types
>>> dict[['list', 'as', 'key']]=3 #lists as keys not possible
Traceback (most recent call last):
 File "<stdin>", line 1, in <module>
TypeError: unhashable type: 'list'
>>> dict["list1"]=['list', 'as', 'value'] #lists as value perfectly fine
```

- Write a function that takes as input a dictionary and returns a new dictionary where keys and values are inverted
- Example:

```
>>> invertDict({'name':'ale', 'age':'impolite to ask', 'nfingers':20})
{'ale':'name', 'impolite to ask':'age', 20:'nfingers'}
```

```
#solution 1
def invertDict(dict):
    newdict = {}
    for (k, v) in dict.items():
        newdict[v] = k
    return newdict
#solution 2
def invertDict(dict):
    newdict = {}
    for key in dict.keys():
        value = dict[key]
        newdict[value] = key
    return newdict
```



- Amino acids are coded in the DNA as codons: a sequence of three bases. Each codon codes for a specific amino acid, but the same amino acid can be coded by more than one codon.
- Write a function that takes as input:
 - 1. a sequence of possible codons (represented as strings, without duplicates)
 - 2. a matching sequence of amino acids (represented as strings, possibly duplicated)
 - 3. a sequence of codons
- And that returns
 - 1. the correct translation of the given codon sequence (3.) into amino acids
- Example:

```
>>> translate(['TTT','TTC','ATT','GCG'], ('Phe','Phe','Ile', 'Ala'), ['ATT','GCG','ATT','GCG','TTT','ATT','GCG'])
['Ile', 'Ala', 'Ile', 'Ala', 'Phe', 'Ile', 'Ala']
```

```
def translate(codons, aminos, seq):
   dict = {}
   for i in range(codons):
        dict[codons[i]] = aminos[i]
        return [dict[el] for el in seq]
```

File I/O

We are going to use only line-oriented file I/O: we read from or write to a file line by line

•

```
>>> infile = open("secretData.txt", 'r') #to read, use open with the 'r' flag
>>> outfile = open("stealData.txt", 'w') #to write, use open with the 'w' flag
                                          #to read a line, 'use readline()'
>>> infile.readline()
"I'm hungry!\n"
                                          #lines end always with a newline character ("n")
>>> outfile.readline()
                                          #you can't read from a file opened for writing
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
io.UnsupportedOperation: not readable
>>> line = infile.readline()
>>> print(line)
                                          \#the trailing '\n' can be annoying
I like pizza!
                                          #that's why here we get an extra blank line
>>> print(line[:-1])
I like pizza!
                                          #we can remove it in this way
>>> line=line.strip()
                                          #or using strip()
                                          #now the last character is '!'
>>> print(line[:-1])
I like pizza
                                          #looping through lines is beautiful
>>> for line in infile:
       print(line.strip())
. . .
. . .
But also ice cream!
Today it's not very sunny...
wazzup bro?
                                          #if we want to re-read a file, we need to close it
>>> infile.close()
>>> infile = open("secretData.txt")
                                          #and open it again
>>> #lines = infile.readlines()
                                          #we can read all lines at once with readlines()
>>> for line in infile:
... outfile.write(line)
                                          #90% of my python scripts look like this
                                          #better to close files at the end
>>> infile.close()
>>> outfile.close()
```

Other important modules

- The random module: generating random numbers
- the re module: pattern matching with regular expressions
- matplotlib and numpy: plotting and scientific computing

The random module

```
>>> import random
>>> random.random()
                                         # Random float x, 0.0 \le x \le 1.0
0.28537541483191564
>>> random.uniform(1, 10)
                                         # Random float x, 1.0 \le x \le 10.0
7.777871877674695
>>> random.randrange(10)
                                         # Integer from 0 to 9
0
>>> random.randrange(0, 101, 2)
                                         # Even integer from 0 to 100
14
>>> random.choice('abcdefqhij')
                                         # Choose a random element in a sequence
'h'
>>> items = [1, 2, 3, 4, 5, 6, 7]
>>> random.shuffle(items)
>>> items
[7, 5, 1, 3, 6, 4, 2]
>>> random.sample([1, 2, 3, 4, 5], 3) #three samples without replacement
[2, 5, 1]
```



- Write a function that takes in an alphabet as a string, a number n and returns a string of length n formed by choosing n times a random character in the alphabet.
- Example:

```
>>> rndString('acgt', 10)
gactggtcag
```

```
import random
#Solution 1:
def rndString(alpha, n):
    res = ""
    for i in range(n):
        res += random.choice(alpha)
    return res
#Solution 2:
def rndString(alpha, n):
    res = [random.choice(alpha) for i in range(n)]
    return "".join(res)
```

Pattern matching with exact patterns

 when we look for exact patterns, there is no need to use the re module, strings already have basic pattern matching capabilities

```
>>> infile = open("secretData.txt", 'r') #to read, use open with the 'r' flag
                                         #to read all lines at once, 'use readlines()': it makes a list of lines
>>> lines = infile.readlines()
["I'm hungry!\n", 'I like pizza!\n', 'But also ice cream!\n', "Today it's not very sunny...\n", 'wazzup bro?\n']
>>> text = "".join(lines)
                                         #str.join() joins all the element in the lists separating them with str
text
"I'm hungry!\nI like pizza!\nBut also ice cream!\nToday it's not very sunny...\nwazzup bro?\n"
                                          #does the pattern 'sistah' occur in the text?
>>> text.find("sistah")
-1
                                          #no
>>> text.find("bro")
                                          #does a bro occur in the text?
                                          #yes, at index 82
82
>>> text[82:(82 + len("bro"))]
                                          #from the index, we can slice off our occurrence from the text
'bro'
                                          #look for pattern "I"
>>> text.find("I")
0
>>> text.find("I", 10)
                                          #look for pattern "I" starting from position 10 (included)
12
>>> text.count("I")
                                          #count occurrences of "I"
2.
>>> text.endswith("bro")
                                          #check pattern at the end of the text (useful for file extensions)
False
>>> text.endswith("bro?\n")
True
>>> text.startswith("I\n")
                                          #check pattern at the beginning
False
>>> text.startswith("I am")
False
>>> text.startswith("I'm")
True
                                         #replace all occurrences of a pattern with another pattern
>>> text.replace("I", "you")
"you'm hungry!\nyou like pizza!\nBut also ice cream!\nToday it's not very sunny...\nwazzup bro?\n"
```

Advanced pattern matching: regular expressions

- The re module handles Perl-style regular expressions (same syntax as in Perl, Unix and many other softwares)
- A good tutorial: https://docs.python.org/3.2/howto/regex.html
- We will focus on Python functions rather than on regular expression syntax

```
>>> import re
                                            #module for regular expressions
>>> text = "that's an ode to the code that I wrote from remote"
>>> pattern = "o.e"
                                            #special character '.' means: any character
>>> m = re.match(pattern, text)
                                            #re.match tests if the entire text matches
                                            #it doesn't
>>> print(m)
None
>>> m = re.search(pattern, text)
                                            #re.search looks for the first match in the text
>>> print(m)
                                            #match object
< sre.SRE Match object at 0x7f864d40b510>
>>> m.start()
                                            #match start
10
>>> m.end()
                                            #match end
13
>>> m.group()
                                            #match content
'ode
                                            #find all the match contents
>>> re.findall(pattern, text)
['ode', 'ode', 'ote', 'ote']
>>> miter = re.finditer(pattern, text)
                                            #sequence of all match objects
>>> ms = list(miter)
                                            #convert it to a list
>>> ms
[<_sre.SRE_Match object at 0x7f864d40b510>,
<_sre.SRE_Match_object_at_0x7f864d40b5e0>,
<_sre.SRE_Match object at 0x7f864d40b648>,
< sre.SRE Match object at 0x7f864d40b6b0>]
>>> [m.start() for m in ms]
                                            #get all starts
[10, 22, 35, 47]
>>> [m.end() for m in ms]
                                           #qet all ends
[13, 25, 38, 50]
>>> [m.group() for m in ms]
                                            #get all contents
['ode', 'ode', 'ote', 'ote']
```

Advanced pattern matching: regular expressions

- regular expressions can represent also variable length matches
- with round brackets we can easily get subsets of the match
- more examples here: http://www.tutorialspoint.com/python/python_reg_expressions.htm

```
>>> text = "dogs are smarter than cats"
                                           #* means repeat the previous pattern any number of times
>>> pattern = r''([a-z]^*) are (\w+) .*"
                                          #+ means repeat the previous pattern at least once
>>> m = re.match(pattern, text)
                                           \#[c-e] means all characters between c and e, same as [cde]
                                           \# \ is a shortcut for [a-zA-Z]
>>> m.group()
'dogs are smarter than cats'
                                           #first round bracket
>>> m.group(1)
'dogs'
                                           #second round bracket
>>> m.group(2)
'smarter'
>>> text = "dogs are smarter than cats, her eyes are blue, they are very good students"
>>> pattern = r"([^ ]*) are (\S*)" #[^abc] means any character ecxept a, b and c
>>> ms = list(re.finditer(pattern, text)) \# is a shortcut for [^ \t nr{fv}]
>>> [m.group() for m in ms]
['dogs are smarter', 'eyes are blue,', 'they are very']
>>> [m.group(1) for m in ms]
['dogs', 'eyes', 'they']
>>> [m.group(2) for m in ms]
['smarter', 'blue,', 'very']
```

Problem: regular expressions

- Given a string 'text' and a character 'c', determine the lengths of all portions of the text where a 'c' appears
- Example:

```
>>> runlengths('aaaaccagaataaataaaa', 'a')
[4,1,2,3,4]
```

Problem: file I/O, read fasta

• Read a file in fasta format. It's more or less like this:



>gi|31563518|ref|NP_852610.1| microtubule-associated proteins 1A/1B light chain 3A isoform b [Homo sapiens] MKMRFFSSPCGKAAVDPADRCKEVQQIRDQHPSKIPVIIERYKGEKQLPVLDKTKFLVPDHVNMSELVKI IRRRLQLNPTQAFFLLVNQHSMVSVSTPIADIYEQEKDEDGFLYMVYASQETFGF

- input: a path to a fasta file
- output: a dictionary with the ids as keys and the sequences as values

```
>>> readFasta('path/to/my/fasta.fasta')
{'id1':'lineline', 'id2':'linelineline'}
```

Problem: file I/O read bed

- Read a file in bed format. It's more or less like this:
 - fields separated by tabs (character '\t')
 - we will care about only the first 3 fields: chromosome, start and end
 - discard lines starting with "#"

#discard m chromosome chromosome	e 1 2	start1 start 2	end1 end2	name1 name2	score 1 score2	strand1 strand2	other-stuff-we-can-ignore1 other-stuff-we-can-ignore2	ignore ignore
chr21 chr22	1000 2000	5000 cl 6000 cl	loneA 960 loneB 900	+ 1000 - 2000	5000 0 2 567, 6000 0 2 433,	488, 0,3512 399, 0,3601		

- input: a path to a bed file
- output: a list of tuples ('chr', start, end)

```
>>> readBed('path/to/my/bed.bed')
[('chr21', 1000, 5000), ('chr22', 2000, 6000)]
```

for real applications, use the Biopython module for python

Problem: file I/O, write fasta

- Read a file in fasta format and a file in bed format, for each tuple ('chr', start, end):
 - slice the sequence with id 'chr' in the fasta file from position start to position end
 - make a new id of the form: id-start-end
 - write this new sequence to an output file in fasta format

chromosome: chromosome:	1 2	start start	1 e: 2 e:	nd1 nd2	name1 name2	5 5	core core	e 1 e2	stı stı	rand1 rand2	other-stuff-we-can-ignore1 other-stuff-we-can-ignore2	ignore ignore
chr21 chr22	1000	5000	cloneA	960 900	+ 1000	5000	02	567, 433	488,	0,3512		

- input:
 - a path to a fasta file
 - a path to a bed file
 - an output path
- output: write in the given file (don't return anything)

>>> getFasta('path/to/my/fasta.fasta', 'path/to/my/bed.bed', 'output/path.fasta')